



U.S. Tsubaki Power Transmission, LLC  
 U.S. Tsubaki Holdings, Inc.  
 Corporate Headquarters  
 301 E. Marquardt Dr.  
 Wheeling, IL 60090 USA

Toll Free: 800.323.7790

Phone: 847.459.9500

Fax: 847.459.9515


Email: [sales@ustsubaki.com](mailto:sales@ustsubaki.com)

Website: [www.ustsubaki.com](http://www.ustsubaki.com)

## HEAVY SERIES CHAINS

**Heavy Series** roller chains differ from the ASME/ANSI standard series in the extra thickness of the link plates and the extra length of the pins. These link plates have the same thickness as the link

[+ more](#)



1 2

<u>Item #</u>	<u>ANSI No.</u>	<u>P - Pitch</u>	<u>R - Roller Diameter</u>	<u>W - Width Between Roller Link Plates</u>	<u>T</u>	<u>Number of Strands</u>	<u>Industry Equivalent</u>	<u>Quantity</u>
<u>60HRB</u>	60	0.750 in	0.469 in	0.500 in	0.125 in	1	N/A	1

<u>Item #</u>	<u>ANSI No.</u>	<u>P - Pitch</u>	<u>R - Roller Diameter</u>	<u>W - Width Between Roller Link Plates</u>	<u>T</u>	<u>Number of Strands</u>	<u>Industry Equivalent</u>	<u>Quantity</u>
<u>60HCB</u>	60	0.750 in	0.469 in	0.500 in	0.125 in	1	N/A	1
<u>80HRB</u>	80	1.000 in	0.625 in	0.625 in	0.156 in	1	N/A	1
<u>80HCB</u>	80	1.000 in	0.625 in	0.625 in	0.156 in	1	N/A	1
<u>100HRB</u>	100	1.250 in	0.750 in	0.750 in	0.187 in	1	N/A	1
<u>100HCB</u>	100	1.250 in	0.750 in	0.750 in	0.187 in	1	N/A	1
<u>120HRB</u>	120	1.500 in	0.875 in	1.000 in	0.219 in	1	N/A	1
<u>120HCB</u>	120	1.500 in	0.875 in	1.000 in	0.219 in	1	N/A	1
<u>140HRB</u>	140	1.750 in	1.000 in	1.000 in	0.250 in	1	N/A	1
<u>140HCB</u>	140	1.750 in	1.000 in	1.000 in	0.250 in	1	N/A	1
<u>160HRB</u>	160	2.000 in	1.125 in	1.250 in	0.281 in	1	N/A	1

<u>Item #</u>	<u>ANSI No.</u>	<u>P - Pitch</u>	<u>R - Roller Diameter</u>	<u>W - Width Between Roller Link Plates</u>	<u>T</u>	<u>Number of Strands</u>	<u>Industry Equivalent</u>	<u>Quantity</u>
<u>160HCB</u>	160	2.000 in	1.125 in	1.250 in	0.281 in	1	N/A	1
<u>200HRB</u>	200	2.500 in	1.562 in	1.500 in	0.375 in	1	N/A	1
<u>200HCB</u>	200	2.500 in	1.562 in	1.500 in	0.375 in	1	N/A	1
<u>240HRB</u>	240	3.000 in	1.875 in	1.875 in	0.500 in	1	N/A	1
<u>240HCB</u>	240	3.000 in	1.875 in	1.875 in	0.500 in	1	N/A	1
<u>60H-2RB</u>	60	0.750 in	0.469 in	0.500 in	0.125 in	2	60-2HRB	1
<u>60H-2CB</u>	60	0.750 in	0.469 in	0.500 in	0.125 in	2	60-2HCB	1
<u>80H-2RB</u>	80	1.000 in	0.625 in	0.625 in	0.156 in	2	80-2HRB	1
<u>80H-2CB</u>	80	1.000 in	0.625 in	0.625 in	0.156 in	2	80-2HCB	1
<u>100H-2RB</u>	100	1.250 in	0.750 in	0.750 in	0.187 in	2	100-2HRB	1

<u>Item #</u>	<u>ANSI No.</u>	<u>P - Pitch</u>	<u>R - Roller Diameter</u>	<u>W - Width Between Roller Link Plates</u>	<u>T</u>	<u>Number of Strands</u>	<u>Industry Equivalent</u>	<u>Quantity</u>
---------------	-----------------	------------------	----------------------------	---	----------	--------------------------	----------------------------	-----------------

<u>100H-2CB</u>	100	1.250 in	0.750 in	0.750 in	0.187 in	2	100-2HCB	1
-----------------	-----	----------	----------	----------	----------	---	----------	---

<u>120H-2RB</u>	120	1.500 in	0.875 in	1.000 in	0.219 in	2	120-2HRB	1
-----------------	-----	----------	----------	----------	----------	---	----------	---

<u>120H-2CB</u>	120	1.500 in	0.875 in	1.000 in	0.219 in	2	120-2HCB	1
-----------------	-----	----------	----------	----------	----------	---	----------	---

<u>140H-2RB</u>	140	1.750 in	1.000 in	1.000 in	0.250 in	2	140-2HRB	1
-----------------	-----	----------	----------	----------	----------	---	----------	---