

U.S. Tsubaki Power Transmission, LLC
 U.S. Tsubaki Holdings, Inc.
 Corporate Headquarters
 301 E. Marquardt Dr.
 Wheeling, IL 60090 USA

Toll Free: 800.323.7790

Phone: 847.459.9500


Fax: 847.459.9515

Email: sales@ustsubaki.com

Website: www.ustsubaki.com

PLASTIC SLEEVE CHAIN

The main characteristic of this chain is that it has an engineering plastic sleeve between the pin and bushing. The engineering plastic roller is also available in combination with the engineering [+ more](#)



1

<u>Item #</u>	<u>P - Pitch</u>	<u>W - Width Between Inner Link Plates</u>	<u>R - Roller Diameter</u>	<u>Approx. Weight</u>	<u>Material</u>	<u>Roller Style</u>	<u>Quantity</u>
<u>CS2040RB</u>	1.000 in	0.312 in	0.312 in	0.296 lbs/ft	Standard	"S" Roller	1
<u>CS2050RB</u>	1.250 in	0.375 in	0.400 in	0.511 lbs/ft	Standard	"S" Roller	1

<u>Item #</u>	<u>P - Pitch</u>	<u>W - Width Between Inner Link Plates</u>	<u>R - Roller Diameter</u>	<u>Approx. Weight</u>	<u>Material</u>	<u>Roller Style</u>	<u>Quantity</u>
<u>CS2060RB</u>	1.500 in	0.500 in	0.469 in	0.914 lbs/ft	Standard	"S" Roller	1
<u>CS2042RB</u>	1.000 in	0.312 in	0.625 in	0.336 lbs/ft	Standard	"R" Roller	1
<u>CS2052RB</u>	1.250 in	0.375 in	0.750 in	0.544 lbs/ft	Standard	"R" Roller	1
<u>CS2062RB</u>	1.500 in	0.500 in	0.875 in	0.974 lbs/ft	Standard	"R" Roller	1
<u>CS2042DRB</u>	1.000 in	0.312 in	0.625 in	0.336 lbs/ft	Standard	"R" Roller	1
<u>CS2052DRB</u>	1.250 in	0.375 in	0.750 in	0.544 lbs/ft	Standard	"R" Roller	1
<u>CS2062DRB</u>	1.500 in	0.500 in	0.875 in	0.974 lbs/ft	Standard	"R" Roller	1
<u>CS2040SSRB</u>	1.000 in	0.312 in	0.312 in	0.296 lbs/ft	Stainless steel	"S" Roller	1
<u>CS2050SSRB</u>	1.250 in	0.375 in	0.400 in	0.511 lbs/ft	Stainless steel	"S" Roller	1
<u>CS2060SSRB</u>	1.500 in	0.500 in	0.469 in	0.914 lbs/ft	Stainless steel	"S" Roller	1

<u>Item #</u>	<u>P - Pitch</u>	<u>W - Width Between Inner Link Plates</u>	<u>R - Roller Diameter</u>	<u>Approx. Weight</u>	<u>Material</u>	<u>Roller Style</u>	<u>Quantity</u>
<u>CS2042SSRB</u>	1.000 in	0.312 in	0.625 in	0.336 lbs/ft	Stainless steel	"R" Roller	1
<u>CS2052SSRB</u>	1.250 in	0.375 in	0.750 in	0.544 lbs/ft	Stainless steel	"R" Roller	1
<u>CS2062SSRB</u>	1.500 in	0.500 in	0.875 in	0.974 lbs/ft	Stainless steel	"R" Roller	1
<u>CS2042SSDRB</u>	1.000 in	0.312 in	0.625 in	0.336 lbs/ft	Stainless steel	"S" Roller	1
<u>CS2052SSDRB</u>	1.250 in	0.375 in	0.750 in	0.544 lbs/ft	Stainless steel	"S" Roller	1
<u>CS2062SSDRB</u>	1.500 in	0.500 in	0.875 in	0.974 lbs/ft	Stainless steel	"S" Roller	1